

10-02-00

A

Please type a plus (+) sign inside this box → ☐

PTO/SB/05 (4/98)

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

JC930 U.S. PTO
09/29/00

UTILITY PATENT APPLICATION TRANSMITTAL <i>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</i>	Attorney Docket No.	00CXT0030C
	First Inventor or Application Identifier	Frank Sacca
	Title	SURGE PROTECTION FOR A DATA ACCESS ARRANGEMENT
	Express Mail Label No.	EL387037089US

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Commissioner for Patents Box Patent Application Washington, DC 20231
---	--

- | | |
|--|---|
| 1. <input checked="" type="checkbox"/> *Fee Transmittal Form (e.g., PTO/SB/17)
<i>(Submit an original and a duplicate for fee processing)</i>
2. <input checked="" type="checkbox"/> Specification [Total Pages <u>26</u>]
<i>(preferred arrangement set forth below)</i>
- Descriptive title of the invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the invention
- Brief Summary of the invention
- Brief Description of the Drawings <i>(if filed)</i>
- Detailed Description
- Claim(s)
- Abstract of the Disclosure
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets <u>4</u>]
4. <input checked="" type="checkbox"/> Oath or Declaration [Total Pages <u>3</u>]
a. <input checked="" type="checkbox"/> Newly executed (original or copy)
b. <input type="checkbox"/> Copy from prior application (37 C.F.R. § 1.63(d))
<i>(for continuation/divisional with Box 16 completed)</i>
i. <input type="checkbox"/> DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b). | 5. <input type="checkbox"/> Microfiche Computer Program <i>(Appendix)</i>
6. Nucleotide and/or amino Acid Sequence Submission <i>(if applicable, all necessary)</i>
a. <input type="checkbox"/> Computer Readable Copy
b. <input type="checkbox"/> Paper Copy (identical to computer copy)
c. <input type="checkbox"/> Statement verifying identity of above copies |
|--|---|

ACCOMPANYING APPLICATION PARTS

- | |
|--|
| 7. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))
8. <input type="checkbox"/> 37 C.F.R. §3.73(b) Statement <input checked="" type="checkbox"/> Power of Attorney
<i>(when there is an assignee)</i>
9. <input type="checkbox"/> English Translation Document <i>(if applicable)</i>
10. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449
<input type="checkbox"/> Copies of IDS Citations
11. <input type="checkbox"/> Preliminary Amendment
12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503)
<i>(Should be specifically itemized)</i>
13. <input type="checkbox"/> *Small Entity Statement(s) (PTO/SB09-12)
<input type="checkbox"/> Statement filed in prior application, Status still proper and desired
14. <input type="checkbox"/> Certified Copy of Priority Document(s)
<i>(if foreign priority is claimed)</i>
15. <input type="checkbox"/> Other: |
|--|

***NOTE FOR ITEMS 1 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).**

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
- | | | | |
|---|-------------------------------------|---|----------------------------------|
| <input type="checkbox"/> Continuation | <input type="checkbox"/> Divisional | <input type="checkbox"/> Continuation-in-part (CIP) | of prior application No.: _____/ |
| Prior application information: Examiner _____ | | Group/Art Unit: _____ | |

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS☐ Customer Number or Bar Code Label*(Insert Customer No. or Attach bar code label here)*or ☒ Correspondence address below

Name	James D. Bennett				
	Akin, Gump, Strauss, Hauer & Feld, L.L.P.				
Address	816 Congress Avenue, Suite 1900				
City	Austin	State	Texas	Zip Code	78701
Country	USA	Telephone	(512) 499-6200	Fax	(512) 499-6290

Name (Print/type)	H. Shannon Tyson, Jr.	Registration No. (Attorney/Agent)	42,193
Signature	<i>H. Shannon Tyson, Jr.</i>	Date	09/29/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

(Attorney Docket No. 00CXT0030C)

TITLE

SURGE PROTECTION FOR A DATA ACCESS ARRANGEMENT

INVENTOR

FRANK SACCA
23036 Rio Lobos Road
Diamond Bar, CA 91765
Citizenship: USA

ASSIGNEE

Conexant Systems, Inc.
4311 Jamboree Road
Newport Beach, CA 92660-3095

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this correspondence, which includes __ pages of Specification and __ pages of Drawings, is being deposited with the United States Postal Service "Express Mail Post Office to addressee" Service under 37 C.F.R. Sec. 1.10 addressed to: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231, on September 29, 2000.

Express Mailing Label No.: US
BL387087089US

Patricia Parks

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

(Attorney Docket No. 00CXT0030C)

TITLE: HIGH-VOLTAGE PROTECTION CIRCUITRY IN A DATA ACCESS ARRANGEMENT

SPECIFICATION**BACKGROUND**

1. Technical Field

The present invention relates generally to communication devices for coupling to an external communication medium; and, more particularly, it relates to a telephone line data access arrangement providing improved surge protection.

2. Related Art

Regulatory agencies throughout the world have established standards and regulations for connecting subscriber equipment to telephone networks. These regulations are intended to prevent damage to the telephone network and mitigate interference with other equipment also connected to the network. The regulations, however, often present difficult design challenges.

According to the applicable regulatory standards of various countries, electrical and electronic equipment imported to or sold in these countries must neither cause excessive electromagnetic interference (EMI) nor be unduly susceptible to it (EMS). Compliance is often demonstrated by performing electromagnetic compliance (EMC) tests to recognized standards. FCC Part 15 (for unlicensed personal communication service devices) is exemplary of the regulatory requirements imposed on radiated or EMI emissions in the United States.

Products that must be tested generally include all electrical and electronic appliances, equipment and installations containing electrical and/or electronic components that are likely to cause or be susceptible to electromagnetic disturbances. A product achieves EMC when it is able

to operate satisfactorily in its intended operating environment without causing EMI to other electronic equipment, and is itself able to operate satisfactorily without being adversely affected by EMI from other equipment operating in the same environment. Failure to pass an EMC compliance test may result in unacceptable delays in reaching the market place, expensive retrofitting of EMI control measures and/or other design modifications, removal of the equipment from the market and monetary penalties.

In addition to stringent EMI requirements, subscriber equipment or data communications equipment (DCE), such as a data modem, is generally required to provide for some form of electrical isolation to prevent voltage surges or transients originating from the subscriber equipment from having a deleterious effect on the telephone network and vice versa. Electrical isolation also addresses potential problems associated with differences in operating voltages between a telephone line and the subscriber equipment. More particularly, telephone line voltages may vary widely across a given network, and often exceed the operating voltage of subscriber equipment. In the United States, 1,500 volt isolation is currently required. In other countries, the prescribed isolation may reach 3,000-4,000 volts.

In the United States, certain of the voltage surge immunity requirements are set forth in the FCC Part 68. As stated therein, a main purpose of the FCC Part 68 Harmonized Requirements is to provide for uniform standards for the protection of a telephone network from harms caused by the connection of terminal equipment and associated wiring. The FCC Part 68 delineates two types of mandatory surge requirements – Type A and Type B surges on the telephone interface, both metallic (or horizontal) and longitudinal (or vertical). As defined in Part 68, Type B surges contain much lower energy than Type A surges. The two types of surges

thus involve different fail-safe criteria. Part 68 compliance requires that both sets of fail-safe criteria be met.

Part 68 defines longitudinal voltage as one half of the vector sum of the potential difference between the TIP connection and earth ground, and the RING connection and earth ground for the TIP, RING pair of 2-wire and 4-wire connections; and, additionally for 4-wire telephone connections, one half of the vector sum of the potential difference between the TIP 1 connection and earth ground and the RING 1 connection and earth ground for the TIP 1, RING 1 pair (where TIP 1 and RING 1 are the receive pair). Part 68 further defines metallic or horizontal voltage as the potential difference between the TIP and RING connections for the TIP, RING pair of 2-wire and 4-wire connections and additionally for 4-wire telephone connections, between the TIP 1 and RING 1 connections for the TIP 1, RING 1 pair (where TIP 1 and RING 1 are the receive pair).

Some communications circuits, such as modems, employ a data access arrangement (DAA) having line side circuitry that includes a telephone (or other) network interface and system side circuitry including a host system interface. The line side circuitry and system side circuitry are separated by a high voltage isolation barrier (e.g., an isolation transformer or capacitive signal paths). Incoming and outgoing TIP and RING signals are generally communicated between line side circuitry and the TIP and RING connections via a diode bridge. Among other functions, the diode bridge prevents electrical damage to the DAA in the event of inverted wires in an RJ-11 jack.

The term DAA generally refers to circuitry, which provides an interface between a public telephone network originating in a central office (CO) and a digital data bus of a host system. The DAA electrically isolates a modem or similar device from a phone line to control emissions

of electromagnetic interference/radio frequency interference (EMI/RFI). In addition to electrical isolation, the DAA often develops a number of signals (e.g., a ring signal) for provision to subscriber equipment. The DAA may receive signals from the phone line through a telephone jack, such as a RJ-11 connection as used for standard telephones.

5 Various circuits have been used to provide surge immunity in such communication circuitry. In a one typical arrangement, the telephone network interface includes a pair of “EMI” capacitors coupled between each of the TIP and RING signal lines and chassis ground or “earth ground”. The EMI capacitors function to shunt relatively high frequency (e.g., 30MHz – 1GHz) emissions to chassis ground in order to reduce EMI radiated emissions from the external
10 telephone cord connected to the RJ11 jack of the DAA. The EMI capacitors may also be used to control longitudinal conducted emissions between TIP/RING and earth ground.

 In addition, a varistor, such as a Metal Oxide Varistor (MOV), is often provided between the TIP and RING signal lines to provide protection from metallic/horizontal surges. The MOV is a voltage clamping device generally capable of absorbing very large currents without damage.
15 By itself, a MOV is capable of holding typical telephone line surge voltages down to a level of approximately 400V peak, or at any other rated voltage specification.

SUMMARY OF THE INVENTION

Briefly, a communication device implemented in accordance with the present invention utilizes a data access arrangement (DAA) having improved surge protection. The DAA incorporates a high voltage clamping device functioning to protect line side circuitry from signal paths created by EMI capacitors.

In one embodiment of the invention, EMI capacitors are added between the “plus” and “minus” terminals of the diode bridge and earth or chassis ground to balance and reduce noise injection onto the TIP and RING lines. These EMI capacitors also reduce EMI interference. However, by adding EMI capacitors on this side (the “rectified side” or “line side”) of the diode bridge, a high voltage signal path to earth ground is created that may have deleterious effects on the line side circuitry.

For example, if a relatively high voltage surge of 1kV is present at the TIP signal (as referenced to the chassis or earth ground), the EMI capacitor between the plus terminal of the diode bridge and chassis ground may become charged to 1,000 volts minus a drop of approximately 1 volt across the diode bridge. However, since the other EMI capacitor between the minus terminal of the diode bridge and chassis ground is initially discharged, the line side circuitry can experience an initial voltage potential of approximately 1,000 volts. Therefore, this longitudinal voltage would appear after the diode bridge as a transient high voltage potential across the line side, and may be sufficient to destroy the line side circuitry, which is typically rated at approximately 400 volts.

More particularly, the line side circuitry may be subjected to excessive voltage for a span of time determined by the equivalent resistance of the line side circuitry and the value of the EMI capacitor(s) between the line side circuitry ground node (minus terminal of the diode bridge) and

the chassis ground. Since line side circuitry is characteristically rated to operate only below certain voltage levels, high voltage energy transients in the line side EMI capacitors during surge conditions may cause the line side circuitry to fail. The typical placement of the MOV on the non-rectified side of the diode bridge does not adequately protect the line side circuitry
5 connected to the rectified side of the diode bridge.

To effectively negate the undesirable signal path through the EMI capacitors to chassis ground, a DAA implemented in accordance with one embodiment of the present invention includes a high voltage clamping device (e.g., a MOV, SIDACTor™, gas discharge tube or similar device) disposed between the plus and minus terminals of the diode bridge for
10 suppressing high voltage spikes. The high voltage clamping device limits the voltage seen by the line side circuitry as a result of high voltage longitudinal surges by providing a current path from the plus terminal to the minus terminal of the diode bridge, thereby effectively bypassing the line side circuitry. The present invention recognizes and takes advantage of the fact that the diodes of a typical diode bridge are capable of withstanding the peak currents associated with most voltage
15 surges. The DAA is thus able to successfully and economically withstand surge voltages when EMI capacitors are added between the plus and minus terminals of the diode bridge to chassis ground, respectively.

Further, a DAA according to the present invention has increased immunity to other problems that may be observed during high-voltage transient tests. Even a metallic or horizontal
20 surge, for example, may be accompanied by a longitudinal spike due to imperfections in the surge generator equipment. Again, such unexpected longitudinal spikes are suppressed by the disclosed DAA.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention can be obtained when the following detailed description of an exemplary embodiment is considered in conjunction with the following drawings, in which:

5 Figure 1 is a schematic diagram of an exemplary data access arrangement incorporating voltage surge protection circuitry in accordance with the present invention;

 Figure 2 is a schematic diagram of an alternate embodiment of a data access arrangement according to the present invention;

 Figure 3 is a schematic diagram providing exemplary details of a communication device
10 utilizing the data access arrangement of Figure 1; and

 Figure 4 is a drawing providing exemplary details of the line side circuitry of the data access arrangement of Figure 1.

Detailed Description

Figure 1 is a schematic diagram of an exemplary data access arrangement (DAA) incorporating voltage surge protection circuitry in accordance with the present invention. In this embodiment of the invention, a high voltage clamping device 100 (*e.g.*, a MOV, SIDACTor™, gas discharge tube or a similar device) is disposed between the plus and minus terminals of a diode bridge 104 for purposes of suppressing high voltage spikes across the line side circuitry. The high voltage clamping device limits the high voltage that may be seen across the line side circuitry as a result of a longitudinal surge applied to the DAA when EMI capacitors 102a and 102b are coupled between the plus and minus terminals of the diode bridge 104 and a chassis ground node, respectively. The high voltage clamping device also limits the effects of metallic surges applied to the DAA. The EMI capacitors 102a and 102b function to balance and reduce noise injection into the TIP and RING signal lines of a telephone connection, and further operate to reduce EMI radiated and conducted emissions.

Although beneficial under certain circumstances, the inclusion of the EMI capacitors on the rectified side of the diode bridge 104 creates a high-voltage signal path from the TIP and RING terminals of the DAA to the chassis ground, exposing the line side circuitry to longitudinal high voltage surges and possibly resulting in deleterious effects on the DAA. For example, if a relatively high voltage surge of 1kV is present at the TIP signal (with reference to the chassis or earth ground), the associated EMI capacitor 102a will become charged to 1,000 volts minus a drop of approximately 1 volt across the diode bridge. However, since the other EMI capacitor 102b between the minus terminal of the diode bridge and chassis ground is initially discharged, the line side circuitry can experience an initial voltage potential of approximately 1,000 volts. Therefore, this longitudinal voltage would appear after the diode bridge as a transient high

voltage potential across the line side, and may be sufficient to destroy the line side circuitry, which is typically rated at approximately 400 volts. The inclusion of the high voltage clamping device, however, allows the DAA to successfully and economically withstand surge voltages by limiting the energy which can be stored in the EMI capacitor 102a and 102b.

5 Referring more particularly to Figure 1, the TIP and RING signal lines of a telephone connection are coupled to a diode bridge 104 in a conventional manner. As known to those of skill in the art, the diode bridge 104 ensures that the same polarity of DC signal is present at its plus and minus terminals regardless of the DC polarity of the TIP and RING connections. Line side circuitry 106 (examples of which are discussed more fully below in conjunction with Figure 10 3 and Figure 4) is coupled between the plus and minus terminals of the diode bridge 104.

In this embodiment of the invention, the EMI capacitor 102a is coupled between the plus terminal of the diode bridge 104 and an earth or a chassis ground node 108. Likewise, the EMI capacitor 102b is coupled between the minus terminal of the diode bridge 104 and a chassis ground node 108. The line side circuitry/device 106 is coupled in a traditional manner between 15 the plus and minus terminals of the diode bridge 104.

In this embodiment of the invention, a voltage clamping device 100 is advantageously coupled between the plus and minus terminals of the diode bridge 104. In this manner, the maximum voltage to which the line side circuitry 106 may be exposed is limited to the voltage rating of the voltage clamping device 100, both for longitudinal and metallic high voltage surges.

20 The voltage clamping device 100 is selected such that transistors and other sensitive circuitry of the line side circuitry 106 are not subjected to a voltage level that causes permanent damage.

The voltage clamping device 100 may take many forms, including a varistor. In one contemplated embodiment, the voltage clamping device 100 is a varistor comprised of a disc of

low-B ceramic material with two tinned solid copper leads. Such varistors may be packaged to be suitable for processing on automatic insertion, cutting and bending equipment to aid in the manufacturing process. Varistors having various maximum voltage and current ratings may be utilized. For example, a varistor having a specified maximum continuous voltage of 175 Vrms
5 (volts root mean square) and a maximum voltage of 410-455 volts at a current of between 5 amps and 50 amps and a maximum non-repetitive transient current in the range of 1,200 amps may be utilized in one embodiment of the invention.

A DAA in accordance with the invention can be utilized with any product that interfaces a telephone network 110 connection to any digital signal processor technology, or any processor
10 of host system circuitry 116 that performs analog modem modulations. Examples include, but are not limited to, data modems, computers, web browsers, set top boxes, home gateway devices, fax machines, cordless telephones and telephone answering machines. In addition, many different interfaces with the telephone network 110 and/or other transmission media are contemplated, such that the DAA may be configured to be compatible with whichever means is
15 utilized.

In addition, the DAA may operate in compliance with one or more standards, such as xDSL. The term "xDSL" is used herein to collectively refer to several different types of DSL technology (e.g., HDSL, VDSL, ADSL, etc.), as well as variants currently under development or yet to be developed. This technology utilizes the local-loop copper connection between a
20 network service provider (NSP) and a customer premises. xDSL is capable of providing simultaneous high-speed digital data access and Plain Old Telephone Service (POTS) over the same twisted-pair wiring. For example, splitterless ADSL componentry, such as that compliant

with the ITU G.lite/G.992.2 specification, may be employed in conjunction with the present invention.

It is further contemplated that the DAA may comply with a number of home networking and communication protocols, such as the Home Phoneline Networking Alliance's (Home PNA) 1M8 (1 Mbps) or 10M8 (10 Mbps) home networking standards, or one of the aforementioned xDSL technologies. A home phone line network compliant with a Home PNA standard may form an Ethernet-compatible LAN running over telephone cabling found in most homes, and does not require any additional hubs, routers, splitters, filters or terminations. Compliant home networking products enable a variety of home computing opportunities, including: shared internet access using a single phone line, printers/peripheral sharing, file and application sharing, and networked gaming. This same home networking technology can also be used to connect a variety of intelligent consumer appliances such as television-based digital set top boxes, internet phones, digital cameras, and multifunction printers.

Figure 2 is a schematic diagram of an alternative embodiment of a DAA according to the present invention. In this embodiment, the DAA of Figure 1 further includes one or more additional voltage clamping devices 110 that are coupled between the TIP and RING signal lines in a traditional manner, as shown in Figure 2. Adding clamping device 110 on the non-rectified side of the diode bridge 104 helps reduce the peak current through the diode bridge 104 during metallic high-voltage surges, by effectively shunting most of the current between TIP and RING before clamping device 100 is activated.

The amount of current flowing through clamping devices 100 and 110 of Figure 2 during high-voltage conditions is largely a function of the voltage rating of the selected devices. In

general, clamping device 100 protects line side circuitry 106 from longitudinal surges and clamping device 110 protects the line side circuitry 106 from metallic surges.

Figure 3 is a schematic diagram providing exemplary details of a communication device using the DAA of Figure 1. The DAA couples the communication device of a host system 216 to the TIP and RING signal lines of a telephone network 202. In addition to the voltage clamping device 100, EMI capacitors 102a and 102b, and diode bridge 104, the DAA comprises a digital isolation barrier 200 for communicatively coupling line side circuitry 106 to system side circuitry 204. The digital isolation barrier 200, in conjunction with features of the line side circuitry 106 that interface with the telephone network 202, provides the necessary level of electrical isolation between the line side circuitry 106 and the corresponding system side circuitry 204.

The digital isolation barrier 200 is designed to comply with both U.S. and international requirements for isolation. In the illustrated embodiment, the digital isolation barrier 200 comprises a single isolation capacitor 210 providing a signal path for bi-directional communication of a serial data stream.

Numerous other embodiments for the digital isolation barrier 200 are contemplated. For example, the digital isolation barrier may comprise a pair of capacitors supporting differential communications, and may further include other circuitry such as a transformer for communicating clock and power signals from this system side circuitry 204 to the line side circuitry 106. Data, control and programming signals may all be communicated between the system side circuitry 204 and the line side circuitry 106.

The system side circuitry 204 of the disclosed embodiment includes a system interface 220 and a digital isolation barrier interface 218a. The system interface 220 coordinates

communications with the host system circuitry 216, while the digital isolation barrier interface 218a establishes communications with the digital isolation barrier 200.

The line side circuitry 106 includes a digital isolation barrier interface 218b corresponding to the digital isolation barrier interface 218a of the system side circuitry 204. The line side circuitry 106 also includes processing circuitry 206 and programmable telephone network interface circuitry 214. Many functions are performed by the programmable telephone network interface circuitry 214, including measuring and establishing electrical parameters that are reflective of the condition of the lines of telephone network 202.

The processing circuitry 206 of Figure 3 includes a coder/decoder (CODEC) 208. The CODEC 208 functions to encode the analog signal on the lines of the telephone network 202 into a digital format, and also provides decoded digital signals for analog transmission over the telephone network 202. In a conventional DAA, a CODEC is disposed on the system side of the high voltage isolation barrier. In the described embodiment, however, the CODEC 208 is advantageously included on the line side of the digital isolation barrier 200 to facilitate communications with the line side circuitry 106. In addition, placement of the CODEC 208 and other circuitry/functions on the line side reduces the number of signals communicated across the digital isolation barrier 200 and facilitates programmability of the network interface circuitry 214.

Programmability of the network interface circuitry 214 may be achieved in a variety of ways. For example, if the host system circuitry 216 desires to program a particular feature of the line side circuitry 106 (e.g., vary line/ring impedance), a command or programming signal is communicated to the system side 204. The command or programming signal may then be reconfigured for transmission to the line side circuitry 106 in a digital manner via the digital

isolation barrier 200. Alternatively, the command or programming signal may originate in the system side circuitry 204, where it will be directed towards the system side circuitry 204 by the line side circuitry 106. Command or programming signals may be multiplexed and serialized for transmission across the digital isolation barrier 200, thereby reducing the complexity and expense of the digital isolation barrier. Data signals may also be combined with command or programming signals, further simplifying the digital isolation barrier 200.

The digital isolation barrier interface 218a of the disclosed embodiment may include clock/power driver circuitry, as well as protocol framing and control circuitry and a transceiver, which coordinate bi-directional transfer of data, control, and programming signals across the digital isolation barrier 200. The clock and power driver circuitry may be responsible for transferring power and clock signals across the digital isolation barrier 200 to the line side circuitry 106, and may be further programmable by the system side circuitry 204 to include a number of different power states, depending on the on-hook status of the DAA.

The system interface circuit 220 may be configured to communicate with the host system 216 in a variety of ways. For example, the system interface circuit 220 may interface directly with a controller-less host architecture. A high-speed serial data interface or a parallel data interface with various I/O lines for modem control and DAA status may also be used. Further, a call progress monitor and a caller ID (CID) control and storage circuit may be included in the system side circuitry 204.

The processing circuitry 206 of the line side circuitry 106, in addition to comprising a CODEC 208, may also include conversion and detection circuitry, such as that described in greater detail below in conjunction with Figure 4. Memory may also be provided by use by the

processing circuitry 206 to store electrical specifications and configurations related to the regulatory requirements of various countries.

Figure 4 is a drawing providing exemplary details of the line side circuitry 106 of the DAA of Figure 1. The line side circuitry 106 may include a variety of programmable functions.

5 For example, programmable measurement circuitry may be provided with adjustable parameters for measuring TIP/RING voltage and loop current conditions on the lines of a telephone network 202, as well as monitoring and execution of commands from the system side circuitry 204. The line side circuitry 106 includes an analog-to-digital space converter (ADC) 290 and a digital-to-analog converter (DAC) 288 for supporting various functionality. The DAC 288 and ADC 290
10 may operate as part of the CODEC 208, or may be separate circuits for use by other components of the line side circuitry 106.

For example, the DAC 288 of the disclosed embodiment is used by a RING/line polarity reversal (LPR) detection circuit 264 and an electronic inductor 276. Similarly, the ADC 290
15 operates in conjunction with the TIP/RING voltage measurement circuit 278 and loop current measurement circuitry 280. The RING/ LPR detection circuitry 264 of the disclosed embodiment is programmable to comply with both U.S. and international requirements. The RING/LPR detection circuitry 264 functions to provide RING wake bit signals. In addition, the RING/LPR detection circuitry 264 is configurable to provide line current sensing information for use by remote on-hook detection circuitry, extension off-hook detection circuitry and digital
20 PBX functions.

It is contemplated that the CODEC 208 of the disclosed embodiment of the invention may be a 16 bit, 16 kHz second order sigma-delta CODEC used for sampling analog signals on the telephone network 202, and to provide such signals to the telephone network 202.

The caller ID circuit 258 receives and decodes caller identification information from the telephone network 202. To this end, it includes a relatively simple ADC and demodulator complying with one or more standards (*e.g.*, V.23/Bell 202, ETSI 300). It is also capable of transferring caller identification information across the digital isolation barrier 200 in a low power state, and is programmable to provide caller ID information without a RING or line polarity reversal.

Signals are provided by the DAA to the telephone network 202 via line driver circuitry 260. The line driver 260 of the disclosed embodiment is programmable to drive signals having the electrical characteristics prescribed by the country in which the DAA is being used. Virtual impedance circuitry 272 is also provided to allow the DAA or host system circuitry 216 to program the electrical characteristics of the DAA as seen by the telephone network 202 to facilitate compliance with a variety of regulatory standards, including country-by-country ring loading. Values measured by the measurement circuitry 256 may be used in this process.

Further contemplated components of the programmable network interface circuitry 214 include, for example: filtering circuitry, pulse dialing circuitry, hook switch circuitry, general purpose I/O lines, line current sensing for digital PBX detection, measurement circuitry for determining Central Office battery and loop DC resistance, line-in use indicators, PABX digital line detection circuitry, and host controlled worldwide DC masks. Many of the disclosed features allow the host system circuitry 216 to easily ascertain the condition of the telephone network 202.

The digital isolation barrier interface 218b of this embodiment includes a protocol framing and control circuit 292 that functions to organize data transmitted by a transceiver 286. The protocol framing circuit 292 also deconstructs signals received by the transceiver 286 from

the system side circuitry 204. In addition, an optional power regulation circuit 282 is provided if the line side circuitry 106 receives power from the system side circuitry 204. Likewise, a clock circuit 284 is provided in the digital isolation barrier interface 218b to receive a signal from the system side circuitry 204 for use in generating clock signals for the logic of the line side circuitry

5 106.

A hybrid circuit 274 is coupled to the CODEC 208 for performing two-wire to four-wire conversion functions and to provide incoming signals to the CODEC 208. A line driver circuit 260 is also coupled to the CODEC 208 and other analog circuitry of the programmable network interface 214. The line driver circuit 260 provides signals from the CODEC 208 to the TIP and

10 RING signal lines.

The analog circuitry of the programmable network interface 214 (which may be considered part of the line side circuitry 106) includes a bipolar junction transistor 320 having an emitter that is coupled to the “+” or plus terminal of the diode bridge 104, while its collector is coupled to a capacitor 322 and a transistor 336. The transistor 320, in conjunction with a resistor

15 334 coupled between its emitter and base, functions to isolate the virtual impedance circuit 272 and the hybrid circuit 274 from the telephone connection when in an on-hook condition. The virtual impedance circuit 272 is coupled to the capacitor 322 via a capacitor 326 and resistor 324, while the hybrid circuit 274 is coupled to the capacitor 322 via resistors 328 and 330 and a capacitor 332. In the disclosed embodiment, these resistors and capacitors provide signal

20 gain/conditioning to allow the virtual impedance circuit 272 and hybrid circuit 274 to operate at a variety of TIP/RING voltage levels. The transistor 320 and the resistor 334 are not required in certain contemplated applications.

The transistor 336 and resistor 338, which are coupled to the line driver circuit 160, allow the line side circuitry 106 to provide signals to the TIP and RING connections 300 and 302 via the diode bridge 104. More specifically, modulation of the base-collector voltage of the transistor 336 allows an AC signal to be presented on the TIP and RING connections 300 and 302.

A transistor 340 having a collector coupled to the base of the transistor 320, in conjunction with the transistor 342, draw line current from the telephone connection for provision to the electronic inductor 276 to indicate off-hook conditions. The electronic inductor 276 operates in conjunction with the DAC 288, ADC 290 and software control functionality of the DAA. The electronic inductor 276 is also coupled to the “+” or plus terminal of the diode bridge 104 via resistors 344, 348, 350 and capacitor 346. The resistor dividers formed of resistors 344 and 348 are utilized to determine if the TIP and RING connection 300 and 302 voltages reflect an on-hook condition.

The loop current measurement circuitry 280 is also coupled to the emitter of the transistor 340 in order to measure current levels present on the TIP and ring conductors 300 and 302. The TIP/RING voltage measurement circuit 278 is coupled to the “+” or plus terminal of the diode bridge 104 via the resistor 344.

The DAC 288 and ADC 290 are utilized in the disclosed embodiment to aid in measuring currents and voltages in the TIP and RING connections 300 and 302, and for providing related information to the protocol framing and control circuit 292 for provision to the system side circuitry 204. The DAC 288 and ADC 290 are programmable to allow modifications to the current and voltages on the TIP and RING connections 303 and 302 (e.g., the line side circuitry

106 can be programmed to draw more current from the TIP and RING connections 300 and 302 to lower telephone line voltages as may be required in a specific country).

Thus, a data access arrangement has been described that includes a high voltage clamping device disposed across the rectified side of a diode bridge for suppressing high voltage spikes.

5 The high voltage clamping device limits the energy that can be stored across EMI capacitors located on the rectified side of the diode bridge. The disclosed embodiment of the invention utilizes the fact that diodes of a typical diode bridge are capable of withstanding peak currents associated with most voltages, and economically improves the surge protection capability of the data access arrangement.

10 In view of the above detailed description of the present invention and associated drawings, other modifications and variations will now become apparent to those skilled in the art. It should also be apparent that such other modifications and variations may be effected without departing from the spirit and scope of the present invention.

CLAIMS

We claim:

1. A data access arrangement for use in a communications device, the data access arrangement circuit comprising:
network interface circuitry;
a diode bridge having a first pair of terminals for coupling data signals to a network connection and a second pair of terminals coupled to the network interface circuitry;
and
a high voltage clamping device disposed between the terminals of the second pair of terminals.

2. The data access arrangement of claim 1, the communications device having a chassis ground, further comprising:
a first capacitor coupled between the chassis ground and one of the terminals of the second pair of terminals; and
a second capacitor coupled between the chassis ground and the other terminal of the second pair of terminals.

3. The data access arrangement of claim 2, further comprising:
at least one additional high voltage clamping device disposed between the terminals of the first pair of terminals.

4. The data access arrangement of claim 2, the communications device having a chassis ground, further comprising:

3 a third capacitor coupled between the chassis ground and one of the terminals of the first
4 pair of terminals; and
5 a fourth capacitor coupled between the chassis ground and the other terminal of the first
6 pair of terminals.

1 5. The data access arrangement of claim 1, wherein the network connection is an RJ-11 jack
2 for coupling to a telephone line.

1 6. The data access arrangement of claim 1, wherein the high voltage clamping device is a
2 metal oxide varistor.

1 7. The data access arrangement of claim 1, wherein the high voltage clamping device is a
2 SIDACTor™.

1 8. The data access arrangement of claim 1, the high voltage clamping device having a
2 maximum specified voltage rating between 410 volts and 455 volts at a maximum specified
3 current rating between 5 amps and 50 amps.

1 9. The data access arrangement of claim 1, further comprising:
2 system side circuitry configurable to communicate with a host system; and
3 a high voltage isolation barrier having a first side and a second side, the first side coupled
4 to the network interface circuitry and the second side coupled to the system side
5 circuitry.

1 10. The data access arrangement of claim 9, the high voltage isolation barrier comprising a
2 capacitor.

1 11. The data access arrangement of claim 1 operating in substantial compliance with an
2 xDSL modem standard.

1 12. The data access arrangement of claim 1 operating in substantial compliance with a home
2 networking protocol.

1 13. A data access arrangement for use in a communications device having a chassis or earth
2 ground, the data access arrangement circuit comprising:

3 network interface circuitry;

4 a diode bridge having a first pair of terminals for coupling data signals to a network
5 connection and a second pair of terminals coupled to the network interface circuitry;
6 and

7 a first high voltage clamping device disposed between the chassis ground and one of the
8 terminals of the second pair of terminals; and

9 a second high voltage clamping device coupled between the chassis ground and the other
10 terminal of the second pair of terminals.

1 14. The data access arrangement of claim 13, the communications device, further comprising:

2 a first capacitor coupled between the chassis ground and one of the terminals of the
3 second pair of terminals; and

4 a second capacitor coupled between the chassis ground and the other terminal of the
5 second pair of terminals.

1 15. The data access arrangement of claim 14, wherein the high voltage clamping device is a
2 metal oxide varistor.

1 16. A communications device comprising:
2 host processing circuitry;
3 system side circuitry coupled to the host processing circuitry;
4 network interface circuitry;
5 a voltage isolation barrier having a first side and a second side, the first side coupled to
6 the network interface circuitry and the second side coupled to the system side
7 circuitry;
8 a diode bridge having a first pair of terminals for coupling data signals to a network
9 connection and a second pair of terminals coupled to the network interface circuitry;
10 and
11 a high voltage clamping device disposed between the terminals of the second pair of
12 terminals.

1 17. The communications device of claim 16 having a chassis ground, further comprising:
2 a first capacitor coupled between the chassis ground and one of the terminals of the
3 second pair of terminals of the diode bridge; and
4 a second capacitor coupled between the chassis ground and the other terminal of the
5 second pair of terminals of the diode bridge.

1 18. The communications device of claim 16, wherein the high voltage clamping device is a
2 metal oxide varistor.

1 19. The communications device of claim 16, wherein the network connection is an RJ-11
2 jack for coupling to a telephone line.

1 20. The communications device of claim 16, the high voltage isolation barrier comprising a
2 capacitor.

ABSTRACT

A data access arrangement (DAA) having improved surge protection. The DAA incorporates a high voltage clamping device functioning to protect line side circuitry from signal paths created by EMI capacitors. In one embodiment of the invention, EMI capacitors are added
5 between the “plus” and “minus” terminals of the diode bridge of the DAA to balance and reduce noise injection onto the TIP and RING lines. These EMI capacitors also reduce EMI interference. However, by adding EMI capacitors on this side (the “rectified side” or “line side”) of the diode bridge, a high voltage signal path to earth ground is created that may have deleterious effects on the line side circuitry. To effectively negate undesirable signal paths
10 through the EMI capacitors, the DAA includes a high voltage clamping device (e.g., a MOV, SIDACTor™, gas discharge tube or similar device) disposed between the plus and minus terminals of the diode bridge for suppressing high voltage spikes. The high voltage clamping device limits the voltage seen by the line side circuitry as a result of high voltage longitudinal surges by providing a current path from the plus terminal to the minus terminal of the diode
15 bridge, thereby effectively bypassing the line side circuitry. The present invention recognizes and takes advantage of the fact that the diodes of a typical diode bridge are capable of withstanding the peak currents associated with most voltage surges.




FIG. 2




FIG. 4

Docket No.: 00CXT0030C

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **SURGE PROTECTION FOR A DATA ACCESS ARRANGEMENT**, the specification of which

(check one) ☒ is attached hereto

☐ was filed on _____ as Application Serial No. _____

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)			<u>Priority Claimed</u>
			Yes/No
(Number)	(Country)	(Date Filed)	
_____	_____	_____	

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application or any international application designating the United States under Title 35, United States Code, §365 listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the

Docket No.: 00CXT0030C

first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56, regarding events which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Number)	(Country)	(Date Filed)
----------	-----------	--------------

(Number)	(Country)	(Date Filed)
----------	-----------	--------------

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

James D. Bennett,	Reg. No. 37,550
H. Shannon Tyson, Jr.,	Reg. No. 42,193
Michael R. Cannatti,	Reg. No. 34,791
Dennis W. Gilstad,	Reg. No. 36,810
Gary W. Hamilton,	Reg. No. 31,834
Gloria L. Norberg,	Reg. No. 36,706
Russell C. Scott,	Reg. No. 43,103
Adam D. Sheehan,	Reg. No. 42,146
Richard J. Smith,	Reg. No. 30,496
Christopher J. Rourk,	Reg. No. 39,348
David R. Clonts,	Reg. No. 36,768
Greg K. Goshorn,	Reg. No. 44,721
George W. Jordan, III,	Reg. No. 41,880
John A. Tang,	Reg. No. 43,404
Richard A. Schafer,	Reg. No. 45,078
R. Scott Rhoades,	Reg. No. 44,300
Shayne X. Short,	Reg. No. 45,105

Of: Akin, Gump Strauss, Hauer & Feld, L.L.P.
816 Congress Avenue, Suite 1900
Austin, TX 78701
(512) 499-6219; and

I also hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Daniel N. Yannuzzi,	Reg. No. 36,727
James K. Dawson,	Reg. No. 41,701
Kelly H. Hale,	Reg. No. 36,542

Docket No.: 00CXT0030C

Robert P. Hart, Reg. No. 35,184
Keith Kind, Reg. No. 42,735
Semion Talpalatsky, Reg. No. 35,380

Address all telephone calls to James D. Bennett at telephone no. (512) 499-6200

Address all correspondence to James D. Bennett
Akin, Gump, Strauss, Hauer & Feld, L.L.P.
816 Congress Avenue
1900 Frost Bank Building
Austin, Texas 78701

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

First named inventor:

Full name Frank Sacca
Inventor's Signature *Frank Sacca* Date Sept. 29, 2000
Residence Diamond Bar, CA Citizenship U.S.
Post Office Address 23036 Rio Lobos Road, Diamond Bar, CA 91765